

ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C ...). The first artifact folder for an artifact type receives the letter A, the second B, etc..

Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB

09244037 BA

Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.

☐

CD(s) containing:

computer program listing

Doc Code: Computer

pages of specification

and/or sequence listing

and/or table

Doc Code: Artifact

content unspecified or combined

Doc Code: Artifact

☐

Artifact Type Code: P

☐

Artifact Type Code: S

☐

Artifact Type Code: U

☐

Stapled Set(s) Color Documents or B/W Photographs

Doc Code: Artifact Artifact Type Code: C

☐

Microfilm(s)

Doc Code: Artifact Artifact Type Code: F

☐

Video tape(s)

Doc Code: Artifact Artifact Type Code: V

☐

Model(s)

Doc Code: Artifact Artifact Type Code: M

☒

Bound Document(s)

Doc Code: Artifact Artifact Type Code: B

☐

Confidential Information Disclosure Statement or Other Documents marked Proprietary, Trade Secrets, Subject to Protective Order, Material Submitted under MPEP 724.02, etc.

Doc Code: Artifact Artifact Type Code X

☐

Other, description: _____

Doc Code: Artifact Artifact Type Code: Z

P009558

The
United
States
of
America



The Commissioner of
Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

Bence Lehman

Commissioner of Patents and Trademarks

Pamela J. Morth

Attest



US005600672A

United States Patent [19]

Oshima et al.

[11] **Patent Number:** **5,600,672**[45] **Date of Patent:** **Feb. 4, 1997**[54] **COMMUNICATION SYSTEM**[75] **Inventors:** Mitsuaki Oshima, Kyoto; Seiji Sakashita, Osaka, both of Japan[73] **Assignee:** Matsushita Electric Industrial Co., Ltd., Osaka, Japan[21] **Appl. No.:** 240,521[22] **Filed:** May 10, 1994**Related U.S. Application Data**

[63] Continuation-in-part of Ser. No. 857,627, Mar. 25, 1992.

[30] **Foreign Application Priority Data**

Mar. 27, 1991	[JP]	Japan	3-62798
Apr. 25, 1991	[JP]	Japan	3-95813
May 29, 1991	[JP]	Japan	3-155650
Jul. 23, 1991	[JP]	Japan	3-182236
Mar. 17, 1992	[JP]	Japan	4-60739
May 10, 1993	[JP]	Japan	5-132984
Sep. 24, 1993	[JP]	Japan	5-261612
Dec. 27, 1993	[JP]	Japan	5-349972
Mar. 24, 1994	[JP]	Japan	6-79668

[51] **Int. Cl.**⁶ H04L 5/16; H04B 1/38[52] **U.S. Cl.** 375/219; 375/270; 375/301; 375/321[58] **Field of Search** 375/219, 259, 375/260, 261, 262, 265, 270, 240, 321, 326, 341, 354; 348/725, 726, 723, 724[56] **References Cited****U.S. PATENT DOCUMENTS**

5,164,963 11/1992 Lawrence et al. 375/265

OTHER PUBLICATIONS

Shanmugam, "Digital and Analog Communication Systems" 1979, p. 272.

Primary Examiner—Stephen Chin*Assistant Examiner*—Hai H. Phan*Attorney, Agent, or Firm*—Wenderoth, Lind & Ponack

[57]

ABSTRACT

At the transmitter side, carrier waves are modulated according to an input signal for producing relevant signal points in a signal space diagram. The input signal is divided into, two, first and second, data streams. The signal points are divided into signal point groups to which data of the first data stream are assigned. Also, data of the second data stream are assigned to the signal points of each signal point group. A difference in the transmission error rate between first and second data streams is developed by shifting the signal points to other positions in the space diagram expressed at least in the polar coordinate system. At the receiver side, the first and/or second data streams can be reconstructed from a received signal. In TV broadcast service, a TV signal is divided by a transmitter into low and high frequency band components which are designated as first and second data streams respectively. Upon receiving the TV signal, a receiver can reproduce only the low frequency band component or both the low and high frequency band components, depending on its capability. Furthermore, a communication system based on an OFDM system is utilized for data transmission of a plurality of subchannels, wherein the subchannels are differentiated by changing the length of a guard time slot or a carrier wave interval of a symbol transmission time slot, or changing the transmission electric power of the carrier.

12 Claims, 178 Drawing Sheets